SEQUENCE™


CP2036/CP2038/CP2040/CP2042/CP2044/CP2046 Indoor pendants — 8" Diameter



VisaLighting.com/products/Sequence

Type: Project: Location:








DIMENSIONS 1, 6


OAH is the distance (in inches) from the bottom of the fixture to the ceiling plane. Example - OAH(192) indicates an overall fixture height of 192"

DIA = Diameter OAH = Overall Height X = Body Height WT = Weight

	CP2036	CP2038	CP2040	CP2042	CP2044	CP2046					
DIA			8" (20	3 mm)							
Standard OAH		192" (4877 mm)									
X with white LED source	26" (660 mm)	37" (940 mm)	49" (1245 mm)	59" (1499 mm)	71" (1803 mm)	93" (2362 mm)					
X with RGB source	23" (584 mm)	35" (889 mm)	47" (1194 mm)	59" (1499 mm)	67" (1702 mm)	90" (2286 mm)					
WT	10 lbs	16 lbs	23 lbs	30 lbs	35 lbs	42 lbs					

CP2046 - STRUCTURAL BLOCKING REQUIRED





FEATURES

- BAA (Buy American Act) and BABA (Build American, Buy America) compliant
- Integral driver
- Modular design for replacement of LED source and driver
- Even illumination
- Color changing RGB LED is DMX-512 compatible (controls by others), See DMX Detail
- Optional LED downlight, 0-10V dimmable (controls by others), with Narrow, Medium, or Wide optical distribtion options
- Power cord is white; cable is stainless steel
- Canopy/Cable/Cord can be shipped ahead to speed installation
- Matte white acrylic cylinder body
- No VOC powder coat paint finish
- ETL listed for damp locations







Buy American Compliant

5 Year Warranty

SEQUENCE (cont.) CP2036/CP2038/CP2040/CP2042/CP2044/CP2046 Indoor pendants — 8" Diameter

BODYLIGHT²

(Optional)

•L30K

L35K

•L40K

•L30K

L35K

•L40K

•RGB



Fill in shaded boxes using information listed below

MVOLT DOWNLIGHT³ **VOLTAGE DOWNLIGHT CANOPY FINISH** OPTION⁵ OAH⁶ **MVOLT** OPTICS⁴ XPS See last page See page 1 (Optional) for finish XPS available MED order codes on models CP2036, NRW CP2038, and WIDE

> Fixture bottom is solid if no downlight is specified

BODYLIGHT SOURCE² (Select one)

MODEL¹

CP2036

CP2038

CP2040

CP2042

CP2044

CP2046

See page 1

CP2046 - STRUCTURAL BLOCKING REQUIRED

CP2040 only

Dimmable 0-10V to 1%, Minimum 85CRI, within 3-step MacAdam

		CP2036		CP2038 CP2040		40	CP2042		CP2044		CP2046			
Source	ССТ	Delivered Lumens	Power/ Watts											
• L30K	3000K	4700		7600		9800		13000		15300		20700		
L35K	3500K	4300 4400	4300	4300	4500 48	86	9000	110	13000	146	15500	171	20/00	233
• L40K	4000K			7800		10100		13400		15700		21400		
• RGB			24		40		56		79		87		118	

Bodylight and downlight are separately switched and controlled/dimmed

DOWNLIGHT SOURCE³

Fixture bottom is solid if no downlight is specified

		CP2036/	CP2038	CP2040/CP2042	2/CP2044/CP2046		
Source	ССТ	Delivered Lumens	Power/ Watts	Delivered Lumens	Power/Watts		
• L30K	3000K	1800		2700			
L35K	3500K	1800	18	2800	28		
• L40K	4000K	1900		2800			

DOWNLIGHT OPTICS4

DOWNLIGHT DETAIL

For downlight only

MED	48° Beam
NRW	34° Beam
WIDE	84° Beam

Rim and Bezel are Painted White



OPTION⁵

XPS Express 10 day shipping. Items marked with a bullet (•) are not available with XPS. XPS available on models CP2036, CP2038 and CP2040 only

VOLTAGE

MVOLT 120-277V, 50/60 Hz


BODYLIGHT LUMEN MAINTENANCE RATING


L80 (reported) >60,000 hrs

DOWNLIGHT LUMEN MAINTENANCE RATING

L80 (reported) >55,000 hrs

PHOTOMETRICS






SEQUENCE (cont.)

CP2036/CP2038/CP2040/CP2042/CP2044/CP2046

Indoor pendants — 8" Diameter



DMX DETAIL



STRUCTURAL BLOCKING DETAIL



CP2046 - STRUCTURAL BLOCKING REQUIRED

SEQUENCE PRODUCT FAMILY

Outdoor	4" Diameter	• OP2232, OP2233, OP2234				
Catenary	8" Diameter	• OP2262, OP2263, OP2264				
Outdoor Cord	4" Diameter	• OP2222, OP2223, OP2224				
and Cable	8" Diameter	• OP2252, OP2253, OP2254				
Outdoor Cham	4" Diameter	• OP2242, OP2243, OP2244				
Outdoor Stem	8" Diameter	• OP2272, OP2273, OP2274				
	4" Diameter	• CP2020, CP2022, CP2024, CP2026, CP2028, CP2030				
Indoor Pendants	8" Diameter	• CP2036, CP2038, CP2040, CP2042, CP2044, CP2046				
	12" Diameter	• CP2052, CP2054, CP2056, CP2058, CP2060, CP2062				
Wall Sconce	Indoor	• CB5201, CB5203				
wan sconce	Outdoor	• 0W5201, 0W5203				

See <u>Visalighting.com/Families/Sequence</u> for more information

SUGGESTED VARIATIONS

- Remote driver
- · Custom colors

SEQUENCE (cont.) CP2036/CP2038/CP2040/CP2042/CP2044/CP2046 Indoor pendants — 8" Diameter



FINISHES

Specify color code when ordering. For accurate color matching, individual paint and finish samples are <u>available upon request</u>. For more information about our finishes visit <u>visalighting.com/finishes</u>

Powder Coat Paint Finishes (Standard)

AGGY	Agate Grey	ALGN	Alpine Green	BMAT	Bronze Matte	BRNZ	Bronze	BSIL	Blade Silver	CVBL	Cove Blue	DEOR	Deoro Gold
GLWT	Glacier White	GSIL	Graphite Siver	HRGR	Harbor Grey	JTBK	Jet Black	OCBL	Ocean Blue	SHGR	Shoreline Grey	SBGN	Sagebrush Green
SLGR	Slate Grey	SSTP	Sierra Taupe	TRCN	Terracotta Canyon	TRWT	Traffic White	VBLK	Velvet Black	VNRD	Vineyard Red	-	