CB1802PSX GIG[™]

Low Voltage – Remote Driver

Rev: 2024/09/16


VISA LIGHTING

VisaLighting.com/products/Gig

Type:

Project:


Location:




DIMENSIONS


Depth is measured from wall to front of fixture

W = Width	H = Height	D = Depth	MC=Fixture edge to mounting center
II IIIacii	ii neigine	D Deptil	The Trikture eage to mounting center





RELATIVE SCALE DRAWING





IP65









VisaLighting.com

FEATURES

- BAA (Buy American Act) and BABA (Build American, Buy America) compliant
- IP65 rated
- IK10+ (100 joules) impact resistant, when BH1 Mounting Bracket is used
- Ligature resistant when BH1 Mounting Bracket is used
- Cast aluminum housing
- 1/4" thick impact resistant polycarbonate lens
- Tamper resistant screws (pin-in-Torx) standard
- Option for Touch dimming control
- Mounts to 2x4 x 1-7/8" deep electrical junction box (by others)
- No-VOC powder coat paint
- Remote driver
 - Use with 24VDC Class II remote power supply and low-voltage Class II wiring between the power supply and the connected fixture. See more information in the Accessories section on page 3
 - A PS24 Series power supply is available from Visa Lighting. This driver must be ordered separately – see Accessories section on page 3 for more information
- ETL listed for wet location

PHOTOMETRICS





NRW (30°)

WIDE (100°)

CB1802PSX GIG (cont.)

VISA LIGHTING

Low Voltage – Remote Driver

Fill in shaded boxes using information listed below 24VDC **CB1802PSX** MODEL SOURCE¹ VOLTAGE **OPTICAL DISTRIBUTION² DIMMING PROTOCOL³** FINISH **OPTION**⁴ L30K(H) 24VDC NRW TOUCHDIM BH1 See last page L30K(L) WIDE Dimmable 0-10V if for finish L35K(H) option is not selected order codes L35K(L)

SOURCE¹ (Select one)

Minimum 80CRI, within 3-step MacAdam									
Source	CCT Range	Delivered Lumens (NRW 27°)	Delivered Lumens (WIDE 100°)	Power (Watts)					
L30K(H)	3000K	300	160	4					
L30K(L)	3000K	150	80	2					
L35K(H)	3500K	300	160	4					
L35K(L)	3500K	150	80	2					

DIMMING PROTOCOL³


Dimmable 0-10V to 1% unless dimming option is selected									
TOUCHDIM Reacts to human touch and cycles between 100%, 50% and off									
0-10V dimming compatible with sinking-type dimmers only (not compatible with sourcing-type dimmers)									

OPTION⁴

BH1

Supplemental Bracket Hardware for high abuse (Pin-In-Torx screws standard with fixture)

HIGH ABUSE SUPPLEMENTAL MOUNTING (BH1) OPTION



VOLTAGE	
24VDC	24 VDC

LUMEN MAINTENANCE RATING

L70	>60,000
L70	>60,000

OPTICAL DISTRIBUTION² (Select one)

Narrow (NRW) is the preferred selection for task lighting

NRW	30°				
WIDE	100° Diffuse				

The NRW option is not "diffuse." It's 30° but uses lenses with direct view





30° optical distribution

100° optical distribution

CB1802PSX GIG (cont.) Low Voltage – Remote Driver



ACCESSORY (Order separately)

PS-24VDC40W01

- 24VDC 40 watt power supply
- When using a single remote 24VDC power supply per fixture it must be suitable for 3W operation
- Multiple units may be powered by a single PS24 power supply. Conductors between fixtures should be sized for $\leq 2\%$ voltage drop at end of wiring run
- See the PS-24 data sheet for any specific switching or wiring limitations
- Express 10 day shipping (XPS) available.

SUGGESTED VARIATION

Custom colors

GIG PRODUCT FAMILY

- CB1800 Integral Driver
- CB1802PSX Low Voltage Remote Driver

See Visalighting.com/products/Gig for more information

FINISHES

Specify color code when ordering. For accurate color matching, individual paint and finish samples are <u>available upon request</u>. For more information about our finishes visit <u>visalighting.com/finishes</u>

Powder Coat Paint Finishes (Standard)

AGGY	Agate Grey	ALGN	Alpine Green	BMAT	Bronze Matte	BRNZ	Bronze	BSIL	Blade Silver	CVBL	Cove Blue	DEOR	Deoro Gold
GLWT	Glacier White	GSIL	Graphite Siver	HRGR	Harbor Grey	JTBK	Jet Black	OCBL	Ocean Blue	SHGR	Shoreline Grey	SBGN	Sagebrush Green
SLGR	Slate Grey	SSTP	Sierra Taupe	TRCN	Terracotta Canyon	TRWT	Traffic White	VBLK	Velvet Black	VNRD	Vineyard Red	-	

This document contains information which is the property of Visa Lighting, and may not, in whole or in part, be duplicated, disclosed, or used for design or manufacturing purposes without the prior written permission of Visa Lighting. ©Visa Lighting. Design Modification Rights Reserved. Visa Lighting reserves the right to change specifications for product improvement without notification.

Rev: 2024/09/16