CP3985 OMNIENCE[™]

34" Diameter - Stem

VISA LIGHTING

Visalighting.com/products/Omnience

Type:

Project:

Location:




DIMENSIONS⁴


🔺 OAH must be specified

OAH is the distance (in inches) from the bottom of the fixture to the ceiling plane. Example - OAH(36) indicates an overall fixture height of 36".

W = Width X = Body Height OAH = Standard Overall Height




RELATIVE SCALE DRAWING



FEATURES

- Integral driver
- Modular design for replacement of LED source and driver
- Upper perforations provide a luminous glow to reduce ceiling contrast if UPLT option is selected
- Mounts through 4" octagonal 2-1/8" deep electrical junction box (by others) with provided hardware for ceiling slopes up to 45° from horizontal
- Rolled extruded aluminum housing
- 1/8" thick diffuser with matte finish • UV stable
- Optional specialty diffuser materials available, including Vara Kamin's Impressions of Light[®] images which are replicated from Vara Kamin's original works of art
- Optional 1/8" thick impact resistant polycarbonate clear lens cover
- No VOC powder coat paint; Low VOC clear coat on metal finishes
- ETL listed for damp locations. Not suitable for exterior applications

PHOTOMETRICS









ETL Listed 5 Year

CP3985 OMNIENCE (cont.)



34" Diameter - Stem

Fill in shaded boxes using information listed below CP3985 MVOLT SOURCE DIFFUSER² OPTION(S)3 0AH4 MODEL VOLTAGE FINISH MVOLT UPLT • L30K IRP L35K See last page XPS See page 1 for finish • L40K order codes

SOURCE¹ (Select one)

Dimmable 0-10V to 1%, Minimum 83CRI within 3-step MacAdam

Sources	CCT	Delivered Lumens	Power (Watts)		
• L30K	3000K	11600	120		
L35K	3500K	11600	120		
• L40K	4000K	12000	120		

VOLTAGE

MVOLT	120-277V, 50/60 Hz	
-------	--------------------	--

DIFFUSER OPTIONS²

Diffuser	' İS	matte	white	acrylic	
----------	------	-------	-------	---------	--

IRP	Impact resistant polycarbonate lens
	impact resistant polycarbonate lens

OPTIONS³ (Multiple selections allowed)

A Option	availability may be interdependent with Other Options
UPLT	Lensed aperture in housing produces 3.8% uplight
XPS	Express 10 day shipping. Items marked with a bullet (•) are not available with XPS

SUGGESTED VARIATIONS

Remote driver
Custom colors

CP3985 OMNIENCE (cont.)

34" Diameter - Stem



OMNIENCE PRODUCT FAMILY

	26" Diameter	• CP3970
Aircraft Cable	34" Diameter	• CP3975
	48" Diameter	• CP3995
	26" Diameter	• CP3980
Stem	34" Diameter	• CP3985
	48" Diameter	• CP3990
Ceiling Mount	26" Diameter	• CM1830

See <u>Visalighting.com/products/Omnience</u> for more information

FINISHES

Specify color code when ordering. For accurate color matching, individual paint and finish samples are <u>available upon request</u>. For more information about our finishes visit <u>visalighting.com/finishes</u>

Powder Coat Paint Finishes (Standard)

AGGY	Agate Grey	ALGN	Alpine Green	BMAT	Bronze Matte	BRNZ	Bronze	BSIL	Blade Silver	CVBL	Cove Blue	DEOR	Deoro Gold
GLWT	Glacier White	GSIL	Graphite Siver	HRGR	Harbor Grey	JTBK	Jet Black	OCBL	Ocean Blue	SHGR	Shoreline Grey	SBGN	Sagebrush Green
SLGR	Slate Grey	SSTP	Sierra Taupe	TRCN	Terracotta Canyon	TRWT	Traffic White	VBLK	Velvet Black	VNRD	Vineyard Red		

This document contains information which is the property of Visa Lighting, and may not, in whole or in part, be duplicated, disclosed, or used for design or manufacturing purposes without the prior written permission of Visa Lighting. ©Visa Lighting. Design Modification Rights Reserved. Visa Lighting reserves the right to change specifications for product improvement without notification.

Rev: 2024/11/25